



PY52 - XX A 01 L=XXXmm

Series NO.	No. of Pos	
	06P 18P	
	08P 20P	
	10P 24P	
	12P 26P	
	14P	
	16P	

cable long
L=XXXmm

注:

1. 裁线时线皮口需切齐不可歪斜.
2. 注意两端IDC连接器压合后的方向.
3. K=K出口纸箱包装, 每一层用隔板隔开.
4. 电气特性符合以下要求:
耐电压:300V, 导通阻抗:3欧, 绝缘阻抗:10M欧

接点图:

P1	1	2	3	X	X	X	24	25	26
P2	1	2	3	X	X	X	24	25	26

1	PUYER UL NO.E485433 PY5201-XXR02BW01 Micro Match 红色IDC 4-26PIN 2件式 2PCS	OPERATION		DRAW	DATE 2021/11/23	SCALE	FIT	普亚电线有限公司 PUYER CABLE CO., LTD HTTP:www.puycable.com			
		X.	±0.20			UNIT	mm				
2	PUYER UL NO.E350147 UL2651 28AWG PH=1.27mm 4-26PIN 灰色红边排线 L=XXXmm 1PCS	X.X	±0.15	CHECK	DATE	SIZE	A4			思展连接器	普亚电线
3		X.XX	±0.10	APPROVE	DATE	SHEET	1/1			TEL:0769-85338949	TEL:0769-85338949
4		ANGLES	±2°			PROJ.		FAX:0769-85338969	FAX:0769-85338969		
		DIM	TOL					MOB:13925839158	MOB:13925839158		
								QQ :530589692	QQ :530589692		