



注:

1. 裁线时线皮口需切齐不可歪斜。
2. K=K出口纸箱包装。
3. 所有材料符合ROHS/REACH
4. 存储温度 15-25度 湿度 30-60%
5. 电气特性符合以下要求:
耐电压:300V, 导通阻抗:3欧, 绝缘阻抗:20M欧

Item	Symbol	Spec
No.of.Conductor (导体芯数)	N	10
Pitch (间距)	P	1.27
Total Width (总宽度)	W	13.97±0.15
Total Pitch (总间距)	TP	11.43±0.15
Margin(边缘宽度)	M	1.27±0.15
Total Length (总长度)	TL	105+2.0
Insulation Length (绝缘长度)	IL	100+2.0
Conductor Strip Length (裸铜长度)	S1	2.5±0.5
	S2	2.5±0.5
Conductor 导体	Tin Plated Ø0.3	
Insulation 绝缘胶	PET 胶膜 0.08mm	
O.V	≤0.7	
C.B	≤0.3	
RoHS Compliance		

1	RFC-1.27*10*105 (2.5/2.5, Ø0.3)	OPERATION		DRAW	DATE 2022/11/02	SCALE	FIT	 普亚电线有限公司 PUYER CABLE CO., LTD HTTP:www.puyercable.com	
		X.	±0.20			UNIT	mm		
		X.X	±0.15	CHECK	DATE	SIZE	A4		
		X.XX	±0.10	APPROVE	DATE	SHEET	1/1		
		ANGLES	±2°			PROJ.			
		DIM	TOL					普亚电线 TEL:0769-85258775 FAX:0769-85251396 MOB:13711962670 QQ :405131416	思展连接器 TEL:0769-85338949 FAX:0769-85338969 MOB:13925839158 QQ :530589692